



# Technical Data Sheet

## D5260 Double-Coated Cloth Tape - Rubber

### Description:

Strong cloth backing with non-residue rubber adhesive. Excellent for carpet hold-down and general purpose use in Aerospace and Automotive.

### Features:

Excellent for temporary or permanent installation. High performance natural rubber leaves no residue when removed.

<u>Physical Characteristics</u>	<u>Standard Values</u>
Carrier .....	Cloth
Carrier Thickness .....	7.0 mil (0.178mm)
Adhesive Type .....	Rubber/Rubber
Adhesive Thickness .....	2.0 mil (0.051mm)/2.0 mil (0.051mm)
180° Peel Adhesion to Stainless Steel .....	40 oz/in (12.0 N/25mm)/ 40 oz/in (12.0 N/25mm)
Available Colors.....	Natural
Liner .....	2 mil blue polyethylene
Total Tape Thickness .....	11.0 mil (0.279 mm)
Tensile Strength .....	20 lbs/in
Holding Power .....	>5 days
Available Lengths .....	25, 36 and Custom

### Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive-to-surface contact.

\*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The Company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.