



## Technical Data Sheet

### # S1017 High Tack Polyester Silicone Splicing Tape

#### Description

S1017 has a 1 mil polyester and a high tack silicone adhesive.

#### Features

Soft, high tack silicone adhesive provides excellent quick-stick to silicone release liners. This tape is also ideal for splicing situations in need of a strong initial stick.

Physical Characteristics	Standard Values
Carrier	1 mil PET
Adhesive Type	Silicone
Adhesive Thickness	2.7 mil – 0.069 mm
180° Peel Adhesion to Stainless Steel	45 oz/in – 13 N/25mm
Tape Color	Green, Red, Blue, or Yellow
Liner	NA
Total Tape Thickness	3.7 mil – 0.094mm
Tensile Strength	40 lbs/in
Available Lengths	72 or 144 yds

#### Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

\*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com  
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405  
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177