



Technical Data Sheet

S1210 Eversplice™ Heavy-Duty Silicone Splicing Tape

Description

S1210 is a silicone splicing tape with a low profile yet high strength splice to release coated surfaces. Its silicone adhesive quickly and permanently bonds to silicone surfaces.

Features

This tape has a high strength polyester backing, and it is easy to handle. The silicone adhesive resists high temperatures, mask slippage, and chemicals, and it bonds excellently to low energy surfaces.

Physical Characteristics	Standard Values
Carrier	2 mil PET
Adhesive Type	Silicone
Adhesive Thickness	1.5 mil – 0.038 mm
180° Peel Adhesion to Stainless Steel	40 oz/in – 11 N/25mm
Tape Color	Green, Blue, Rust, Red, or Clear
Liner	NA
Total Tape Thickness	3.5 mil – 0.089 mm
Temperature Resistance	400°F – 205°C
Available Lengths	72 yds

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177