



Technical Data Sheet

S3115 Tan Flatback Sealing Tape

Description

S3115 is a medium strength flatback tape.

Features

This tape increases efficiency as a result of its superior initial quick-stick adhesion and the ability to be hand-torn. It also performs well in many different temperatures and humidity conditions.

Physical Characteristics	Standard Values
Carrier	Paper-Flatback
Adhesive Type	Rubber
Adhesive Thickness	NA
180° Peel Adhesion to Stainless Steel	57 oz/in – 15.5 N/25mm
Tape Color	Tan
Liner	NA
Total Tape Thickness	6.0 mil – 0.15 mm
Service Temperature Range	45°F to 100°F – 7°C - 38°C
Available Lengths	36 and 60 yards

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177