



## Technical Data Sheet

# # S3300 Low Tack Paper Protective Tape

### Description

S3300 has a printable fibrous paper backing with a rubber adhesive.

### Features

The paper backing is coated with a latex P/S adhesive which removes cleanly. The stable backing doesn't stretch, making it perfect for protecting highly polished surfaces. This product is not for use outdoors.

Physical Characteristics	Standard Values
Carrier	Paper-Crepe
Adhesive Type	Rubber
Adhesive Thickness	NA
180° Peel Adhesion to Stainless Steel	13.5 oz/in – 4 N/25mm
Tape Color	White
Liner	NA
Total Tape Thickness	4.2 mil – 0.107 mm
Tensile Strength	17 lbs/in – 8 kg/25mm
Available Lengths	60 yds

### Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

\*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com  
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405  
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177