



Technical Data Sheet

S3330 White Removable Floor Marking Tape

Description

S3330 is a paper tape with a non-residue adhesive. Ideal for Gym floors where removability is critical.

Features

This tape removes easily from most floor surfaces without residue or floor damage. Hand-tear ability provides easy application.

Physical Characteristics	Standard Values
Carrier	4 mils Flatback Paper
Adhesive Type	Rubber
Adhesive Thickness	1.5 mil – 0.038 mm
180° Peel Adhesion to Stainless Steel	25 oz/in – 7 N/25mm
Tape Color	White
Liner	NA
Total Tape Thickness	5.5 mil – 0.140 mm
Tensile Strength	30lbs/in
Available Lengths	36/55/60 yds

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177