



**ChampionTM
Tape**

Technical Data Sheet

S3340

White Artist's Tape

Description

S3340 is a premium grade tape with a smooth white backing.

Features

Smooth backing provides an excellent surface for printing on with standard flexographic inks, writing on with pen or markers, painting, map edging, writing on, labeling, finishing the edges of a presentation board, identification, lightweight packaging, and bag locking.

Physical Characteristics	Standard Values
Carrier	Paper
Adhesive Type	Rubber
Adhesive Thickness	NA
180° Peel Adhesion to Stainless Steel	35 oz/in – 9.5 N/25mm
Tape Color	White
Liner	NA
Total Tape Thickness	6.0 mil – 0.15 mm
Tensile Strength	25 lbs/in – 13 kg/25mm
Available Lengths	NA

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177