



## Technical Data Sheet

# # S4250 Hook & Loop Fastener Tape

### Description

S4250 is a loop tape coated with a pressure sensitive adhesive. This Loop product is used in conjunction with our Hook Fastener Product.

### Features

Rubber adhesive provides excellent adhesion to a range of surfaces while the sturdy woven nylon backing provides long usage. The loop fastener has a densely napped pile of loops, designed for repeated openings and closings.

<b>Physical Characteristics</b>	<b>Standard Values</b>
Carrier	Hook & Loop
Adhesive Type	Rubber
Adhesive Thickness	3 mil – 0.076 mm
180° Peel Adhesion to Stainless Steel	200 oz/in – 55 N/25mm
Tape Color	Black or White
Liner	Paper/Film
Total Tape Thickness	NA
Holding Power (PSTC-7) 1000g	NA
Available Lengths	Various

### Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

\*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com  
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405  
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177