



Technical Data Sheet

D5710 Double-Sided Crepe Paper Tape

Description

D5710 has a high-quality saturated crepe paper, double-coated with a high tack, high shear synthetic rubber-based adhesive.

Features

This tape provides superior tack on irregular surfaces as well as excellent shear and high tack abilities.

Physical Characteristics	Standard Values
Carrier	6 mil Crepe Paper
Adhesive Type	Rubber
Adhesive Thickness (each side)	1 mil – 0.051 mm
180° Peel Adhesion to Stainless Steel	110 oz/in – 30 N/25mm
Tape Color	Beige
Liner	3.2 mils White Silicone Release Paper
Total Tape Thickness	8.0 mil – 0.20 mm
Holding Power (PSTC-7) 1000g	>3 days
Available Lengths	36 and 60 yards

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177