



Technical Data Sheet

S4563 Smooth Printer's Anti-Slip Tape

Description

S4563 has an impregnated and silicone coated cloth backing which prevents slippage.

Features

The impregnated and silicone coated cloth backing provides anti-slip adhesive properties. The rubber adhesive is temperature resistant.

Physical Characteristics	Standard Values
Carrier	15.5 mil Siliconized Cloth
Adhesive Type	Rubber
Adhesive Thickness	1.3 mil – 0.033 mm
180° Peel Adhesion to Stainless Steel	27 oz/in – 7.4 N/25mm
Tape Color	Grey
Liner	Polypropylene Film
Total Tape Thickness	16.8 mil – 0.425 mm
Service Temperature (Short/Long Term)	302°F/212°F – 150°C/100°C
Available Lengths	27 yds

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177