

Technical Data Sheet

D5715

Double-Coated Polyester Tape

Description

D5715 is a thin PET film double-coated with a rubber-based pressure sensitive adhesive and self-wound on a Kraft liner. Product has a firm adhesive ideal for diecutting.

Features

For general purpose solutions and bonding to smooth surfaces. Excellent bonding for paper, metal, plastics and most low plasticized materials. Excellent Quick tack.

Physical Characteristics	Standard Values
Carrier	.5 mil PET Film
Adhesive Type	Rubber
Adhesive Thickness (each side)	2.25 mil – 0.057 mm
180° Peel Adhesion to Stainless Steel	128oz/in – 35.46 N/25mm
Tape Color	Clear
Liner	Kraft
Total Tape Thickness	2.9 mil – 0.074 mm
Holding Power (PSTC-7) 1000g	350+ hrs
Available Lengths	36/60/72 yds

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.