



## Technical Data Sheet

# # D6000 Double Coated Repulpable

### Description

2 Mil double coated repulpable splice tape. Ideal for manual and automatic splicing in the paper making industry. Quickly soluble in cool and hot water.

### Features

Excellent Tack and peel.  
Bonds to a variety of paper products.  
Easily recognizable with its green tint

Physical Characteristics	Standard Values
Carrier	1.4 mil tissue
Adhesive Type	Repulpable Acrylic
Adhesive Thickness (each side)	4.4 mil -- 0.112 mm
180° Peel Adhesion to Stainless Steel	38 oz/in – 10 N/25mm
Tape Color	Clear or Green
Liner	Double Coated Liner (White)
Total Tape Thickness	5.5 mil – 0.140 mm
Heat Resistance	>205C
Available Lengths	36/60 yards

### Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

\*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com  
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405  
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177