



Technical Data Sheet

S3125

Gaffer's Tape

Description

S3125 has a vinyl coated cloth for indoor and outdoor use.

Features

The vinyl coated cloth backing provides conformability to irregular surfaces as well as protection against the weather. This tape is also photographer-friendly due to its non-reflective properties.

Physical Characteristics	Standard Values
Carrier	Cloth
Adhesive Type	Rubber
Adhesive Thickness	NA
180° Peel Adhesion to Stainless Steel	55 oz/in – 15 N/25mm
Tape Color	Black or White
Liner	NA
Total Tape Thickness	13.0 mil – 0.330 mm
Tensile Strength	45 lbs/in – 20 kg/25mm
Available Lengths	36 yards

Tape Application

To achieve ultimate adhesion, the bonding surfaces should be dry, clean and free of dirt and oils. The strength of the adhesion bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

*Note: Values should be used for specification purposes and are averages taken from PSTC and ASTM test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Champion Tape serves you better. Contact our team for qualified application support.

www.championtape.com
Phone 888-580-8588, 262-598-7400 Fax 262-598-7405
7900 Durand Ave. Bldg. 4, Sturtevant WI 53177